Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method of embedding digital watermark information
b₁ - bn (2 ≤ n) in image data, comprising steps of:

dividing the image data into a plurality of areas S each consisting of $M \times N$ (1 $\leq M$, N) pixels;

defining a plurality of areas G each an area G consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S;

allocating each of the areas S constituting each area said area G to some one of: areas T_1 - T_n which said digital watermark information b_1 - b_n , a bit value of the digital watermark information being 0 or 1, is respectively embedded whose pixel values are changed and areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded whose pixel values are not changed;

corresponding each of said T_1 - T_n whose pixel values are changed, to each of said digital watermark information b_1 - b_n and changing the pixel value of each area T according to a bit value;

locating areas T_1 - T_n and areas H_1 - H_m in a predetermined same arrangement in each said area G; and

locating the plurality of areas G in a predetermined rule locating said area G repeatedly, wherein

said location of said areas G thus located repeatedly is not dependent on said digital watermark information.

2. (currently amended) A method of embedding digital watermark information
b₁ - b₁ (2 ≤ n) in image data, comprising steps of:

dividing the image data into a plurality of areas S each consisting of $M \times N$ (1 $\leq M$, N) pixels;

defining a plurality of areas G each an area G consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S;

allocating each of the areas S constituting each-said area G to some one of: areas T_1 - T_n in which said digital watermark information b_1 - b_n , a bit value of the digital watermark information being 0 or 1, is respectively embeddedwhose pixel values are changed, areas J_1 - J_k ($1 \le k$) in which information p_1 - p_k ($1 \le k$) specifying an embedding format for embedding said digital watermark information b_1 - b_n in said areas T_1 - T_n , and areas H_1 - H_m ($1 \le m$) in which any of bit information 0 and 1 is not embeddedwhose pixel values are not changed;

corresponding each of said T_1 - T_n whose pixel values are changed, to each of said digital watermark information b_1 - b_n and changing the pixel value of each area T according to a bit value;

locating areas T_1 - T_n , areas J_1 - J_k and areas H_1 - H_m in a predetermined same arrangement in each said area G; and

locating the plurality of areas G in a predetermined rule locating said area G repeatedly, wherein

said location of said areas G thus located repeatedly is not dependent on said digital watermark information.

3. (original) The method of embedding digital watermark information according to Claim 2, wherein:

said digital watermark information b_1 - b_n is embedded by increasing or decreasing pixel data values in the corresponding areas T_1 - T_n according to a bit value (0, 1) of each bit of the digital watermark information b_1 - b_n ; and

said information p_1 - p_k specifying said embedding format is embedded such that said information indicates a pattern of respective increasing/decreasing directions in the area T_1 - T_n for a bit value of the digital watermark information, in each area G to which the areas J_1 - J_k embedded with said information p_1 - p_k belong.

4. (previously presented) The method of embedding digital watermark information according to Claim 1, wherein:

each of said areas G includes said areas H_1 - H_m which have been predetermined in a location so as to be asymmetric in vertical and horizontal directions in the area G in question.

5. (currently amended) A method of extracting digital watermark information, for extracting the digital watermark information $b_1 - b_n$ ($2 \le n$), a bit value of the digital watermark information being 0 or 1, from image data in which said digital

watermark information is embedded, comprising steps of:

dividing the image data into a plurality of areas S each consisting of $M \times N$ (1 $\leq M$, N) pixels;

detecting areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S;-and

recognizing a plurality of areas G each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S, said plurality of areas G areas T_1 - T_n being located on said image data, and said recognition being carried out by comparing locations of said detected areas H_1 - H_m on said image data and locations of predetermined areas H_1 - H_m in the areas S_1 and

extracting the digital watermark information b_1 - b_n from the recognized areas T_1 - T_n .

6. (previously presented) A method of extracting digital watermark information, for extracting the digital watermark information b_1 - b_n ($2 \le n$), a bit value of the digital watermark information being 0 or 1, from image data in which said digital watermark information is embedded, comprising steps of:

dividing the image data into a plurality of areas S each consisting of M × N (1 \leq M, N) pixels; detecting areas H₁ - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S;

recognizing a plurality of areas G each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S, said plurality of areas G being located on said image data, and said recognition being carried out by comparing locations of said detected areas H_1 - H_m

on said image data and locations of predetermined areas H₁ - H_m in the areas S;

in each of the plurality of areas G recognized, extracting information p_1 - p_k (1 \leq k) from areas J_1 - J_k in which said information p_1 - p_k (1 \leq k) in which said information p_1 - p_k (1 \leq k) should be embedded, said information p_1 - p_k specifying an embedding format for embedding said digital watermark information b_1 - b_n respectively in said areas T_1 - T_n ;

recognizing the embedding format of the digital watermark information b_1 - b_n in the areas T_1 - T_n in the area G in question; and

extracting the digital watermark information b_1 - b_n from the areas T_1 - T_n , according to the recognized embedding format.

7. (original) The method of extracting digital watermark Information according to Claim 6, wherein:

for each of the plurality of groups G recognized, the information p_1 - p_k embedded in the areas J_1 - J_k is extracted to recognize a pattern of increasing/decreasing directions of pixel data values for a bit value of the digital watermark information, in the area G in question; and

each bit value of the digital watermark information b_1 - b_n embedded in the areas T_1 - T_n is detected according to the recognized pattern of increasing/decreasing directions.

8. (previously presented) The method of extracting digital watermark information according to Claim 5, wherein a plurality of areas H are detected from

each of the areas G;

the detected areas H are compared with a predetermined location in the areas H_1 - H_m , said predetermined location being determined in advance such that the areas H become asymmetric in vertical and horizontal directions in the area G in question; and

contents of image processing carried out on the image data are judged.

9. (currently amended) A program product for making a computer execute a method of embedding digital watermark information $b_1 - b_n$ ($2 \le n$), a bit value of the digital watermark information being 0 or 1, in image data, comprising:

codes for dividing the image data into a plurality of areas S each consisting of $M \times N \ (1 \le M, N)$ pixels;

codes for defining a plurality of areas G an area G each consisting of P × Q (1 ≤ P, Q) of the areas S;

codes for allocating each of the area S constituting each-said area G to some one of: areas T_1 - T_n in which said digital watermark information b_1 - b_n is respectively embedded whose pixel values are changed and areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded whose pixel values are not changed;

codes for corresponding each of said T_1 - T_n whose pixel values are changed, to each of said digital watermark information b_1 - b_n and changing the pixel value of each area T according to a bit value;

codes for locating one or more areas T_1 - T_N and one or more areas H_1 - H_m in a predetermined same arrangement in each said area G;

codes for locating the plurality of areas G in a predetermined rule codes for locating said area G repeatedly, wherein

said location of said areas G thus located repeatedly is not dependent on said digital watermark information; and

a computer readable storage medium for holding the codes.

10. (currently amended) A program product for making a computer execute a method of embedding digital watermark information $b_1 - b_n$ ($2 \le n$) in image data, comprising:

codes for dividing the image data into a plurality of areas S each consisting of $M \times N \ (1 \le M, N)$ pixels;

codes for defining a plurality of areas G each an area G consisting of P × Q (1 ≤ P, Q) of the areas S;

codes for allocating each of the areas S constituting each-said area G to some one of: areas T_1 - T_n in which said digital watermark information b_1 - b_n is respectively embedded whose pixel values are changed, areas J_1 - J_k ($1 \le k$) in which information p_1 - p_k ($1 \le k$) specifying an embedding format for embedding said digital watermark information b_1 - b_n , a bit value of the digital watermark information being 0 or 1, in said areas T_1 - T_n , and areas H_1 - H_m ($1 \le m$) in which any of bit information 0 and 1 is not embedded whose pixel values are not changed;

codes for corresponding each of said T_1 - T_n whose pixel values are changed, to each of said digital watermark information b_1 - b_n and changing the pixel value of each area T according to a bit value;

codes for locating one or more areas T_1 - T_n , and areas J_1 – J_k in a predetermined same arrangement in each said area G;

codes for locating the plurality of areas G in a predetermined rule codes for locating said area G repeatedly, wherein

said location of said area G thus located repeatedly is not dependent on said digital watermark information; and

a computer readable storage medium for holding the codes.

11. (original) The program product according to Claim 10, further comprising: codes for embedding said digital watermark information b₁ - b_n by increasing or decreasing pixel data values in the corresponding areas T₁ - T_n according to a bit value (0, 1) of each bit of the digital watermark information b₁ - b_n; and

codes for embedding said information p_1 - p_k specifying said embedding format such that said information indicates a pattern of respective increasing/decreasing directions in the areas T_1 - T_n for a bit value of the digital watermark information, in each area G to which the areas J_1 - J_k embedded with said information p_1 - p_k belong.

12. (previously presented) The program product according to Claim 9, wherein:

each of said areas G includes a plurality of said areas H_1 - H_m which have been predetermined in a location so as to be asymmetric in vertical and horizontal directions in the area G in question.

13. (currently amended) A program product for making a computer execute a method of extracting digital watermark information b_1 - b_n (2 \leq n), a bit value of the digital watermark information being 0 or 1, from image data in which said digital watermark information is embedded, comprising:

codes for dividing the image data into a plurality of areas S each consisting of $M \times N$ (1 $\leq M$, N) pixels;

codes for detecting areas H_1 - H_m (1 $\leq m$) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S;

codes for recognizing a plurality of areas $G_{\underline{1}-\underline{1}_n}$ each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S, said plurality of areas $G_{\underline{1}-\underline{1}_n}$ being located on said image data, and said recognition being carried out by comparing locations of said detected areas H_1 - H_m on said image data and locations of predetermined areas H_1 - H_m in the areas S;

codes for extracting the digital watermark information b_1 - b_n from the recognized areas T_1 - T_n ; and

a computer readable storage medium for holding the codes.

14. (previously presented) A program product for making a computer execute a method of extracting digital watermark information $b_1 - b_n$ ($2 \le n$), a bit value of the digital watermark information being 0 or 1, from image data in which said digital watermark information is embedded, comprising:

codes for dividing the image data into a plurality of areas S each consisting of

 $M \times N (1 \leq M, N)$ pixels;

codes for detecting areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S codes for recognizing a plurality of areas G each consisting of P × Q (1 \leq P, Q) of the areas S, said plurality of areas G being located on said image data, and said recognition being carried out by comparing locations of said detected areas H_1 - H_m on said image data and locations of predetermined areas H_1 - H_m in the areas S;

codes for extracting, in each of the plurality of areas G recognized, information $p_1 - p_k$ ($1 \le k$) from areas $J_1 - J_k$ in which said information $p_1 - p_k$ ($1 \le k$) should be embedded, said information $p_1 - p_k$ specifying an embedding format for embedding said digital watermark information $b_1 - b_n$ respectively in said areas $T_1 - T_n$;

codes for recognizing the embedding format of the digital watermark information b_1 - b_n in the areas T_1 - T_n in the area G in question;

codes for extracting the digital watermark information b_1 - b_n from the areas T_1 - T_n , according to the recognized embedding format; and a computer readable storage medium for holding the codes.

15. (original) The program product according to Claim 14, further comprising: codes for extracting, for each of the plurality of groups G recognized, the information p₁ - p_k embedded in the areas J₁ - J_k, to recognize a pattern of increasing/decreasing directions of pixel data values for a bit value of the digital watermark information, in the area G in question, and to detect each bit value of the

digital watermark information b_1 - b_n embedded in the areas T_1 - T_n according to the recognized pattern of increasing/decreasing directions.

16. (original) The program product according to Claim 13, further comprising: codes for detecting a plurality of areas H from each of the areas G;

codes for comparing the detected areas H with an embedding pattern for the areas H, said embedding pattern being determined in advance such that the areas H become asymmetric in vertical and horizontal directions in the area G in question;

and

codes for judging contents of image processing carried out on the image data.

17. (currently amended) An apparatus for embedding digital watermark information $b_1 - b_n$ (2 \leq n) in image data, comprising:

a processing part for dividing the image data into a plurality of areas S each consisting of M \times N (1 \leq M, N) pixels;

a processing part for defining a plurality of areas G each an area G consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S;

a processing part for allocating each of the areas S constituting each-said area G to some one of: areas T_1 - T_n in which said digital watermark information b_4 - b_n , a bit value of the digital watermark information being 0 or 1, is respectively embedded whose pixel values are changed and areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded whose pixel values are not changed;

a processing part for corresponding each of said T₁ - T_n whose pixel values

are changed, to each of said digital watermark information b₁ - b_n and changing the pixel value of each area T according to a bit value;

a processing part for locating one or more areas T₁ - T_n, and one or more areas H₁ - H_m in a predetermined same arrangement in each-said area G; and a processing part for locating the plurality of areas G in a predetermined rule a processing part for locating said area G repeatedly, wherein

said location of said areas G thus located repeatedly is not dependent on said digital watermark information.

18. (currently amended) An apparatus for embedding digital watermark information $b_1 - b_n$ (2 $\leq n$) in image data, comprising:

a processing part for dividing the image data into a plurality of areas S each consisting of M \times N (1 \leq M, N) pixels;

a processing part for defining a plurality of areas G each an area G consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S;

a processing part for allocating each of the areas S constituting each said area G to some one of: areas T_1 - T_n in which said digital watermark information b_1 - b_n , a bit value of the digital watermark information being 0 or 1, is respectively embedded whose pixel values are changed, areas J_1 - J_k ($1 \le k$) in which information p_1 - p_k ($1 \le k$) specifying an embedding format for embedding said digital watermark information b_1 - b_n in said areas T_1 - T_n , and areas H_1 - H_m ($1 \le m$) in which any of bit information 0 and 1 is not embedded whose pixel values are not changed;

a processing part for corresponding each of said T₁ - T_n whose pixel values

are changed, to each of said digital watermark information b₁ - b_n and changing the pixel value of each area T according to a bit value;

a processing part for locating one or more areas T_1 - T_n , one or more areas J_1 - J_k and one or more areas H_1 - H_m in a predetermined same arrangement in each said area G; and

a processing part for locating the plurality of areas G in a predetermined rulea processing part for locating said area G repeatedly, wherein

said location of said areas G thus located repeatedly is not dependent on said digital watermark information.

19. (original) The apparatus for embedding digital watermark information according to Claim 18, further comprising:

a processing part for embedding said digital watermark information b_1 - b_n by increasing or decreasing pixel data values in the corresponding areas T_1 - T_n according to a bit value (0, 1) of each bit of the digital watermark information b_1 - b_n ; and

a processing part for embedding said information p_1 - p_k specifying said embedding format such that said information indicates a pattern of respective increasing/decreasing directions in the area T_1 - T_n for a bit value of the digital watermark information, in each area G to which the areas J_1 - J_k embedded with said information p_1 - p_k belong.

20. (previously presented) The apparatus for embedding digital watermark

information according to Claim 17, wherein:

each of said areas G includes a plurality of areas H_1 - H_m which have been predetermined in a location so as to be asymmetric in vertical and horizontal directions in the area G in question.

21. (currently amended) An apparatus for extracting digital watermark information $b_1 - b_n$ ($2 \le n$), a bit value of the digital watermark information being 0 or 1, from image data in which said digital watermark information is embedded, comprising:

 \downarrow a processing part for dividing the image data into a plurality of areas S each consisting of M × N (1 ≤ M, N) pixels;

a processing part for detecting areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S; and

a processing part for recognizing a plurality of areas G areas $T_1 - T_n$ each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S, said plurality of areas G areas $T_1 - T_n$ being located on said image data, and said recognition being carried out by comparing locations of said detected areas $H_1 - H_m$ on said image data and locations of predetermined areas $H_1 - H_m$ in the areas S: and

a processing part for extracting the digital watermark information b_1 - b_n from the recognized areas T_1 - T_n .

22. (previously presented) An apparatus for extracting digital watermark information $b_1 - b_n$ (2 $\leq n$), a bit value of the digital watermark information being 0 or

1, from image data In which said digital watermark information is embedded, comprising:

a processing part dividing the image data into a plurality of areas S each consisting of M \times N (1 \leq M, N) pixels;

a processing part for detecting areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S;

a processing part for recognizing a plurality of areas G each consisting of P × Q (1 \leq P, Q) of the areas S, said plurality of areas G being located on said image data, and said recognition being carried out by comparing locations of said detected areas H₁ - H_m on said image data and locations of predetermined areas H₁ - H_m in the areas S; a processing part for extracting, in each of the plurality of areas G recognized, information p₁ - p_k (1 \leq k) from areas J₁ - J_k in which said information p₁ - p_k (1 \leq k) should be embedded, said information p₁ - p_k specifying an embedding format for embedding said digital watermark information b₁ - b_n respectively in said areas T₁ - T_n;

a processing part for recognizing the embedding format of the digital watermark information b_1 - b_n in the areas T_1 - T_n in the area G in question; and a processing part for extracting the digital watermark information b_1 - b_n from the areas T_1 - T_n , according to the recognized embedding format.

23. (original) The apparatus for extracting digital watermark information according to Claim 22, further comprising:

a processing part for extracting, for each of the plurality of groups G

recognized, the information p_1 - p_k embedded in the areas J_1 - J_k , to recognize a pattern of increasing/decreasing directions of pixel data values for a bit value of the digital watermark information, in the area G in question, and to detect each bit value of the digital watermark information b_1 - b_n embedded in the areas T_1 - T_n , according to the recognized pattern of increasing/decreasing directions.

24. (previously presented) The apparatus for extracting digital watermark information according to Claim 21, further comprising:

a processing part for detecting a plurality of areas H from each of the areas G;

Jand

a processing part for comparing the detected areas H with a predetermined location in the areas H_1 - H_m , said predetermined location being determined in advance such that the areas H become asymmetric in vertical and horizontal directions in the area G in question; and

a processing part for judging contents of image processing carried out on the image data.

25. (previously presented) An apparatus for embedding digital watermark information $b_1 - b_n$ (2 \leq n) in image data, comprising:

a processor; and

a storage unit for storing codes for making the processor execute a method of embedding the digital watermark information; wherein:

said codes comprises:

codes for dividing the image data into a plurality of areas S each consisting of $M \times N \ (1 \le M, N)$ pixels;

codes for defining a plurality of areas G each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S;

codes for allocating each of the areas S constituting each area G to some one of: areas T_1 - T_n in which said digital watermark information b_1 - b_n , a bit value of the digital watermark information being 0 or 1, is respectively embedded, areas J_1 - J_k , (1 \leq k) in which information P_1 - P_k (1 \leq k) specifying a embedding format for embedding said digital watermark information b_1 - b_n in said areas T_1 - T_n , and areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded; codes for locating one or more areas T_1 - T_n , one or more areas T_1 - T_n , and one or more areas T_1 - T_n , and area T_1 - T_n , and area T_1 - T_n are area T_1 - T_n and area T_1 - T_n are area T_1 - T_n and area T_1 - T_n are area T_1 - T_n and area T_1 - T_n are area T_1 - T_n and area T_1 - T_n are area T_1 - T_n are area T_1 - T_n are area.

codes for locating the plurality of areas G in a predetermined rule.

26. (previously presented) An apparatus for extracting digital watermark information b_1 - b_n (2 \leq n), a bit value of the digital watermark information being 0 or 1, from image data in which said digital watermark information is embedded, comprising:

a processor; and

a storage unit for storing codes for making the processor execute a method of extracting the digital watermark information; wherein:

said codes comprises:

codes for dividing the image data into a plurality of areas S each consisting of $M \times N \ (1 \le M, N)$ pixels;

codes for detecting areas H_1 - H_m (1 \leq m) in which any of bit information 0 and 1 is not embedded, from said plurality of areas S;

codes for recognizing a plurality of areas G each consisting of $P \times Q$ (1 $\leq P$, Q) of the areas S, said plurality of areas G being located on said image data, and said recognition being carried out by comparing locations of said detected areas H_1 - H_m on said image data and locations of predetermined areas H_1 - H_m in the areas S; and codes for extracting, in each of the plurality of areas G recognized, information $p_1 - p_k$ (1 $\leq k$) from areas $J_1 - J_k$ in which said information $p_1 - p_k$ (1 $\leq k$) should be embedded, said information $p_1 - p_k$ specifying an embedding format for embedding said digital watermark information $p_1 - p_n$ respectively in said areas $T_1 - T_n$.